

















MODEL	CARRERA mm	L mm	L min. mm	Ø D mm	Ø d mm	 daN	 daN	Base Cilindro Cylinders Bases	Version Especial Special Version
Y 300-10	10	70	60	32	16	300	~ 550		—
Y 300-13	13	75.4	62.7						
Y 300-16	16	82	66						
Y 300-25	25	100	75						
Y 300-38	38	126	88						
Y 300-50	50	150	100						
Y 300-63	63	177	113.5						
Y 300-80	80	210	130						
Y 300-100	100	250	150						
Y 300-125	125	300	175						
Y 500-10	10	70	60	38	20	500	~ 1050		—
Y 500-13	13	75.4	62.7						
Y 500-16	16	82	66						
Y 500-25	25	100	75						
Y 500-38	38	126	88						
Y 500-50	50	150	100						
Y 500-63	63	177	113.5						
Y 500-80	80	210	130						
Y 500-100	100	250	150						
Y 500-125	125	300	175						
Y 700-13	13	110.4	97.7	45	24	700	~ 1100		
Y 700-25	25	135	110						
Y 700-38	38	161	123						
Y 700-50	50	185	135						
Y 700-63	63	212	148.5						
Y 700-80	80	245	165						
Y 700-100	100	285	185						
Y 700-125	125	335	210						
Y 700-160	160	405	245						
Y 1000-13	13	120.4	107.7	50	30	1000	~ 1750		
Y 1000-25	25	145	120						
Y 1000-38	38	171	133						
Y 1000-50	50	195	145						
Y 1000-63	63	222	158.5						
Y 1000-80	80	255	175						
Y 1000-100	100	295	195						
Y 1000-125	125	345	220						
Y 1000-160	160	415	255						
Y 1000-200	200	495	295						
Y 1000-250	250	595	345						
Y 1000-300	300	695	395						

MODEL	CARRERA mm	L mm	L min. mm	Ø D mm	Ø d mm	 daN	 daN	Bases Cilindros <i>Cylinders Bases</i>	Version especial <i>Special Version</i>
Y 2400-25	25	160	135	75	45	2400	~ 4250		
Y 2400-38	38	186	148						
Y 2400-50	50	210	160						
Y 2400-63	63	237	173.5						
Y 2400-80	80	270	190						
Y 2400-100	100	310	210						
Y 2400-125	125	360	235						
Y 2400-160	160	430	270						
Y 2400-200	200	510	310						
Y 2400-250	250	610	360						
Y 2400-300	300	710	410						
Y 4200-25	25	170	145	95	60	4200	~ 7700		
Y 4200-38	38	196	158						
Y 4200-50	50	220	170						
Y 4200-63	63	247	183.5						
Y 4200-80	80	280	200						
Y 4200-100	100	320	220						
Y 4200-125	125	370	245						
Y 4200-160	160	440	280						
Y 4200-200	200	520	320						
Y 4200-250	250	620	370						
Y 4200-300	300	720	420						
Y 6600-25	25	190	165	120	75	6600	~ 12500		
Y 6600-38	38	216	178						
Y 6600-50	50	240	190						
Y 6600-63	63	267	203.5						
Y 6600-80	80	300	220						
Y 6600-100	100	340	240						
Y 6600-125	125	390	265						
Y 6600-160	160	460	300						
Y 6600-200	200	540	340						
Y 6600-250	250	640	390						
Y 6600-300	300	740	440						